

订货信息

CCA – B-CD-EFGH-IJ

A – 线缆类别.

FCX = 防火同轴

B – 标准

RG6 = RG 6之类; FRRG6 = 防火 RG 6之类

C – 屏蔽类型

BC = 铜丝编织; TC = 镀锡铜编织; 铝= 铝丝/铝带;

D – 屏蔽密度

60 = 60%; 80 = 80%

E- 内衬/内护套

Y = PVC; 2Y = PE; H = 低烟无卤;

F – 铠装

SWA = 钢丝铠装; STA = 钢带铠装; SWB = 钢丝编织铠装; DSTA = 双层钢带铠装

G – 护套

Y = PVC; Yu = 防火PVC; Yv = PVC加强护套; 2Y = PE; H = 低烟无卤;

H – 导体结构

7(0.14) = 7/0.14mm

I – 防火等级 (可选)

1 = IEC 332-1; 3C = IEC 60332 = 3C; 3A = 60332-3A

J – 防火标准 (可选)

331 = IEC 331; 6386CWZ = BS 6387 CWZ

举例说明:

CCFCX-RG6-铝100/TC61-H(SWA)H-1/0.95-3A

防火同轴系列, RG6, 100%铝箔屏蔽+61%镀锡铜编织, 低烟无卤内护套, 钢带铠装, 低烟无卤护套, 1/0.95mm, 防火等级遵循IEC 332-3A